

PRODUCT SPECIFICATIONS

8256

6' ViewPack® Energy Absorbing Lanyard, Single-leg with Steel Snap Hooks

CONTACT SALES

Built for harsh and abrasive environments, this lanyard combines heavy-duty polyester webbing with a smooth-decelerating energy absorber. The ViewPack inspection window helps improve inspection visibility and label protection.

Features :

- Heavy-duty 1" polyester web construction throughout
- Energy absorber features patented ViewPack® cover with inspection window.
- ViewPack® cover also features WrapPack label protection
- Includes alloy steel snap hooks for harness attachment and anchorage connection
- Complies with ANSI Z359.13-2013



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
ANSI	Z359.13-2013
OSHA	1926.502 and 1910.66

Sizes & Part Numbers		
8256 (ANSI Compliant)	C8256 (CSA Compliant)	