

6814150K

Rescue and Descent Worksite Kit with Storage Bag

CONTACT SALES

Designed for jobsite readiness, this complete rescue and descent kit delivers controlled lowering capability in a portable, easy-to-store package. The included storage bag helps keep rescue equipment organized and accessible when every second counts.

Features :

- 7/16" sheathed-core kernmantle rope lifeline resists moisture and abrasion for longer life
- Integral triple-mode lifting capability includes handwheel, ratcheting handle and power drill adapter.
- Telescoping Ratchet lifting handle adjusts from 12" to 18" for unmatched rescue lifting leverage
- Bi-directional design provides shuttle operation for multiple successive descending users
- Rope lifeline features aluminum alloy connectors for lighter weight
- Device features integral belay hooks and swiveling aluminum attachment carabiner
- Also includes 6' pass through choker anchor and 28" backpack style storage bag
- Complies with ANSI Z359.4-2013



Material Specifications		Performance Specifications	
Rope	7/16" kernmantle polyamide blend	Max Descent Height	524' for 2 users
Connectors	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength	Max Descent Load	440 lb for 2 users
Housing	Powder coated aluminum	Descent Speed	2.6' per second for 1 user
		Cumulative Descent Distance	25,200' or 48 descents with 220 lb
		Cumulative Descent Distance	2,620' or 5 descents with 440 lb
		Max Lifting Height	524' at 440 lb
		Max Work Lifting Load	308 lb

Compliant With:	
ANSI	Z359.4 2013

Sizes & Part Numbers				
681450K - 50'	6814150K - 150'	6814300K - 300'	6814500K - 500'	