

TRADESMAN PRO

7008C

Tradesman® Pro 1D Standard Non-belted Full Body Harness, Tongue Buckle Leg Adjustments

CONTACT SALES

Features :

- Features all black plated alloy steel hardware for refined, low profile look
- V-slot locking D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day
- Dorsal attachment tunnel allows for fast, hassle-free connection of single or twin SRL-Ps and keeps them optimally positioned on the back reducing fatigue
- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Plated alloy steel low profile spring tension roller torso adjusters provide simple upper body adjustment
- Quick-connect buckle features visual indicators showing positive connection
- Tongue buckle legs provide quick and simple lower-body adjustment
- Includes suspension trauma relief straps
- Complies with ANSI Z359.11 2021



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-ring	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.11-2021
CSA	Z259.10-2018
OSHA	1926.502 and 1910.66

Sizes & Part Numbers			
7008CSM Dual Size Small/Med	7008CLX Dual Size Large/XL	7008C2X3X Dual Size 2XL/3XL	