

DURATECH®

72706SB1

6' DuraTech® Mini Class 1 Personal SRL-P with Steel Snap Hook, Includes Steel Dorsal Connecting Carabiner

CONTACT SALES

When every ounce counts, the DuraTech Mini SRL delivers big protection in a compact package. With impact-resistant housing, a high-strength Dyneema® lifeline, and a ViewPack® energy absorber for smooth deceleration, the DuraTech Mini gives you the protection you can count on, without breaking the bank.

Features :

- Features internal locking pawls and ViewPack® external energy absorber for even deceleration
- Long-wearing Dyneema® web lifeline resists abrasion while providing trusted strength.
- Nylon housing provides impact resistance in most worksite conditions
- Plated steel swivel eye helps to prevent lifeline twisting and provide smooth operation
- Features alloy steel snap hook anchorage connector
- Includes alloy steel dorsal connecting carabiner
- May be anchored up to 5' below the dorsal D-ring with no edge hazards for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14 2021 Class 1 SRL P.
[Learn more and download White Paper](#)



Material Specifications	
Webbing	Dyneema®/Polyester blend; 4,500 lb min.
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 1 SRL P
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
ANSI	Z359.14 2021
OSHA	1926.502 and 1910.66
CSA	Z259.2.2 2017

Sizes & Part Numbers		
72706SB1 (ANSI Compliant)	C72706SB1 (CSA Compliant)	