

# DURATECH®

## 72706TB1

6' DuraTech® Mini Class 1 Personal SRL-P with Steel Snap Hooks, Includes Steel Dorsal Connecting Carabiner

### CONTACT SALES

When every ounce counts, the DuraTech Mini SRL delivers big protection in a compact package. With impact-resistant housing, a high-strength Dyneema® lifeline, and a ViewPack® energy absorber for smooth deceleration, the DuraTech Mini gives you the protection you can count on, without breaking the bank.

#### Features :

- Features internal locking pawls and ViewPack® external energy absorbers for even deceleration
- Long-wearing Dyneema® web lifeline resists abrasion while providing trusted strength.
- Nylon housings provide impact resistance in most worksite conditions
- Plated steel swivel eyes help to prevent lifeline twisting and provide smooth operation
- Features alloy steel snap hook anchorage connectors
- Includes alloy steel dorsal connecting carabiner with twin-leg alignment clip
- May be anchored up to 5' below the dorsal D-ring with no edge hazards for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14 2021 Class 1 SRL P.

[Learn more and download White Paper](#)



| Material Specifications |                                                                               |
|-------------------------|-------------------------------------------------------------------------------|
| Webbing                 | Dyneema®/Polyester blend; 4,500 lb min.                                       |
| Energy Absorber         | Polyester tear-away                                                           |
| Anchorage Connector     | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |
| Dorsal Connector        | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |

| Performance Specifications |                    |
|----------------------------|--------------------|
| Static Strength            | 3,600 lb min.      |
| ANSI SRL Class/Type        | Class 1 SRL P      |
| Avg. Arrest Force          | 900 lb             |
| Max. Arrest Force          | 1,800 lb           |
| Max. Arrest Distance       | 42"                |
| ANSI User Capacity         | 130 to 310 lb max. |
| OSHA User Capacity         | 130 to 310 lb max. |

| Compliant With: |                      |
|-----------------|----------------------|
| ANSI            | Z359.14 2021         |
| OSHA            | 1926.502 and 1910.66 |
| CSA             | Z259.2.2 2017        |

| Sizes & Part Numbers         |                              |  |
|------------------------------|------------------------------|--|
| 72706TB1<br>(ANSI Compliant) | C72706TB1<br>(CSA Compliant) |  |