

PRODUCT SPECIFICATIONS

7372

Pass-through Choker Anchor with Heavy-duty Wear Pad

CONTACT SALES

Designed for repeated choke-on applications, this abrasion-resistant web anchor combines durable wear protection with flexible pass-through installation for temporary anchorage around structures and beams.

Features :

- Features 1-3/4" load-bearing web with 3" wide full-length wear pad for abrasion resistance
- Appropriately sized alloy steel D-rings provide simple pass-through choke-on installation.
- May be passed through multiple times to shorten length
- Smaller D-ring facilitates connection point for SRLs and lanyards
- Each D-ring termination features three individual 2" box-stitches for longer life
- Complies with ANSI Z359.18-2017



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Plated alloy steel; 5,000 lb min. static strength
Wear Pad	3" Polyester webbing

Performance Specifications	
Static Strength	5,000 lb min.
ANSI User Capacity	136 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.18-2017
OSHA	1926.502 and 1910.66
CSA	Z259.15-2017

Sizes & Part Numbers								
7324 2' (ANSI Compliant)	7336 3' (ANSI Compliant)	C7336 3' (CSA Compliant)	7348 4' (ANSI Compliant)	7372 6' (ANSI Compliant)	C7372 6' (CSA Compliant)	737208 8' (ANSI Compliant)	737210 10' (ANSI Compliant)	7373 12' (ANSI Compliant)
C7373 12' (CSA Compliant)	737214 14' (ANSI Compliant)	737220 20' (ANSI Compliant)	737224 24' (ANSI Compliant)	737230 30' (ANSI Compliant)				