

BEAM-LOCK

7540A14

BeamLock™ Anchor, Dual Adjustment, 4" to 14"

CONTACT SALES

This mobile beam anchor combines dual-adjusting jaws and low-friction wear pads to deliver smooth, hands-free trailing movement across structural steel beams while maintaining a secure anchorage connection.

Features :

- Includes two sizes of replaceable wear pads: traditional short wear pads for all applications and new long wear pads for a true hands-free, snag-free walking experience in trailing applications
- Features aluminum crossbar and steel clamping jaws with wear pads
- Fits beam flanges from 4" to 14" wide and up to 1-1/4" thick.
- Dual adjusting jaws include concealed locking thumb latches
- Alloy steel D-ring remains centered on crossbar
- For temporary mobile use on horizontal I-beams
- Complies with ANSI Z359.18-2017



Material Specifications	
D-ring	Plated alloy steel; 5,000 lb min. static strength
Crossbar	Aluminum alloy
Clamp Jaws	Aluminum alloy
Wear Pads	Nylon

Performance Specifications	
Static Strength	5,000 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.18-2017
OSHA	1926.502 and 1910.66