

772100

100' 4-Person Temp Rope HLL System

CONTACT SALES

Built for larger crews and demanding jobsites, this temporary rope HLL system supports up to four workers while maintaining fast installation and dependable performance. An integrated energy absorber and included anchorage hardware help simplify setup and improve jobsite efficiency.

Features :

- High-strength, durable 5/8" double braid polyester rope lifeline with steel thimble and stitched end-termination
- Exclusive line tensioner assembly with integral energy absorber and anchorage-end carabiner.
- Includes 4 connecting rings, 2 heavy duty pass through anchor straps, and additional thimble end carabiner
- 18" gear bag provides suitable storage and transportation of the HLL system
- Meets OSHA 1926.502 regulations



Material Specifications	
Rope	5/8" Double-braid Polyester Rope; 6,000 lb min. static strength
Connecting Rings	Plated alloy steel; 5,000 lb min. static strength
Carabiners	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Sling Anchors	Polyester webbing with plated alloy steel D-rings; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Tensioner	Aluminum alloy and stainless steel; 6,000 lb min. static strength

Performance Specifications	
User Capacity	max. 4 users. 130 lb up to 310 lb each
System Strength	6,000 lb Min Static Strength

Compliant With:

OSHA	1926.502
-------------	----------

Sizes & Part Numbers			
772030 30'	772060 60'	772100 - 100'	