

77602K

60' Temporary Rope HLL System; 2-person with Kernmantle Rope

CONTACT SALES

Built for demanding temporary fall protection applications, this two-person rope HLL system combines durable kernmantle rope with integrated energy absorption for dependable performance and efficient setup in the field.

Features :

- Features 11/16" solid-core nylon kernmantle rope with one sewn and thimbled end-termination
- Plated steel line tensioner features integrated energy absorber with carabiner.
- Also includes 2 pass through anchors, 2 connecting rings, additional carabiner and storage bag
- Meets OSHA 1926.502 and 1910.66 regulations



Material Specifications	
Rope	11/16" braided 32-strand solid-core nylon kernmantle; 5,000 lb min.
Sling Anchors	Polyester webbing with plated alloy steel D-rings; 5,000 lb min. static strength
Carabiners	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Tensioner and Connecting Rings	Plated alloy steel; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away

Performance Specifications	
Static Strength	5,000 lb min.
OSHA User Capacity	310 lb max. per user; 2 users max.

Compliant With:	
OSHA	1926.502 and 1910.66

Sizes & Part Numbers			
77302K 30'	77602K 60'	771002K - 100'	