



Calculate Your
Fall Clearance

AXIS
By FallTech®

84108TP5

8' FT-X® EdgeCore™ Class 2 Leading Edge Personal SRL-P, Twin-leg with Aluminum Rebar Hooks with SpeedLink™

CONTACT SALES

The FT-X EdgeCore sets the standard for Class 2 SRLs with its streamlined design and revolutionary, Kevlar®-reinforced EdgeCore lifeline—stronger and lighter than comparable steel cables. Built for the toughest environments, this segment-leading SRL features the groundbreaking SpeedLink design for fast retractable leg replacements, keeping you safe, efficient, and ready without missing a beat.

Features :

- EdgeCore™ lifeline is made from Kevlar® cables and a UV-resistant composite jacket, weighing 40% less than 3/16" galvanized cable used in most Class 2 SRL-P's
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features comprehensive fall clearance charts and tables inside the energy absorber cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- Features SpeedLink™ field replaceability of damaged retractable units, lowering overall cost of ownership and reducing equipment down time [Request SpeedLink™ Spanner Tool](#)
- Replacement retractable part number is 84108RP5
- **AXIS™ enabled:** Easily and accurately calculate minimum fall clearance with the AXIS safety calculator on your mobile device or computer
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. [Learn more and download White Paper](#)



Material Specifications	
Lifeline	EdgeCore™; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Anchorage Connector	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Aluminum alloy; 3,600 lb min.

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 2 SRL P
Avg. Arrest Force	1,350 lb max.
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 420 lb max.

Compliant With:	
ANSI	Z359.14 2021
OSHA	1926.502 and 1910.66
CSA	Z259.2.2 2017