

PRODUCT SPECIFICATIONS



6050428WR

5pc Confined Space Davit System with 12" to 29" Offset Davit Arm, Winch and SRL-R

CONTACT SALES

Features :

- Davit arm adjusts from 12" to 29" offset reach to keep lifelines centered over access locations
- Base width adjusts from 38" to 65" and fits a wide range of openings.
- 5pc system features 33" lower mast extension and 2 device receiver brackets
- Includes 60' galvanized cable SRL-R and Personnel Winch
- Offset davit arm features two pulleys and secondary 5,000 lb anchor point
- 3pc base includes integral bullseye level and tool-free height adjustment
- Lightweight powder coated aluminum combined with alloy steel for longer life and durability
- Davit System meets OSHA 1926.502 and 1910.66 regulations
- SRL-R complies with ANSI Z359.14-2014, Winch complies with ANSI Z359.4-2013



Material Specifications

Davit System	Powder coated 6061 aluminum and plated steel
---------------------	--

Performance Specifications

Rescue Static Strength	5,000 lb min.
Entry/Egress Static Strength	1,800 lb min.
Rescue User Capacity	2 users, 310 lb max. for each person
Entry/Egress Capacity	1 user, 310 lb max.

Compliant With:

OSHA	1926.502 and 1910.66
-------------	----------------------