

7016

Contractor 1D Standard Non-belted Full Body Harness, Tongue Buckle Leg Adjustment

CONTACT SALES

The Contractor harness delivers essential support for working at height—economical, secure, and built to get the job done. Adjustable torso and leg straps ensure a wide fit range, while paired lanyard keepers keep gear out of the way. When you're focused on essential safety, the Contractor has your back.

Features :

- Plated alloy steel mating buckle torso adjusters deliver economical fit
- Features tongue buckle leg connections with 7 grommeted leg adjustment positions for a wide range of fit
- Paired lanyard parking keepers provide balanced function for single and double-leg lanyards
- Plated alloy steel dorsal D ring with mating buckle chest and tongue buckle leg closures
- Complies with ANSI Z359.11-2014



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-ring	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.11-2014
OSHA	1926.502 and 1910.140
CSA	Z259.10-2018

Sizes & Part Numbers				
7016XS XS	7016 - UniFit (S, M, L)	7016X/2X Dual size XL/2X	70163X 3X	