

7016B

Contractor+ 1D Standard Non-belted Full Body Harness

CONTACT SALES

The Contractor+ harness delivers essential support with added comfort for working at height. A padded air-mesh shoulder yoke adds breathable cushioning, while adjustable torso and leg straps ensure a wide fit range. Paired lanyard keepers keep gear out of the way. When essential safety is your priority, the Contractor+ has your back.

Features :

- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple adjustment
- Breathable padded air-mesh shoulder yoke delivers added user comfort
- Paired lanyard parking keepers provide balanced function for single and twin leg personal SRLs
- Plated alloy steel dorsal D-ring with mating buckle chest and tongue buckle leg closures
- Features tongue buckle leg connections with 7 grommeted leg adjustment positions for a wide range of fit
- Complies with ANSI Z359.11-2021



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-ring	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.11-2021
OSHA	1926.502 and 1910.140
CSA	Z259.10-2018

Sizes & Part Numbers			
7016BXS XS	7016B UniFit (S, M, L)	7016BX/2X Dual size XL/2X	