



## MAXIMIZING THE POTENTIAL OF THE EXPONENTIAL UPGRADE.

# ZENITH X2 MAX ANSI



### STANDARD

ANSI Z89.1 Type I Type II, Class E HT-LT  
All around protection against impact and penetration including front, rear, and sides.

### EN 12492

for the following clauses only:  
Shock energy absorption capacity  
4.2.1.2 front impact, 4.2.1.3 lateral impact,  
4.2.1.4 rear impact  
4.2.2 Penetration  
4.2.3 Retention system strength  
4.2.4 Effectiveness of the retention system



### SIZE

Adjustable – from 60 to 66 cm



### MATERIAL

EXTERNAL SHELL:  
HD Polypropylene



### INTERNAL SHELL:

**Neopor® Cycled®** by BASF | EPS  
obtained from chemical recycling  
of plastic waste.

HEADBAND:  
Soft PA Nylon



### TEMPERATURE OF USE

-22°F / +140°F



### WEIGHT

1.19 lb



WHE00134

○ 201	● 204	● 209
● 202	● 205	● 210
● 203	● 208	● 215

## TECHNOLOGIES

- **D-CORE & HD-CROWN TECHNOLOGY** Neopor® Cycled® internal shell that protects from all-around impacts.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- **ELECTRIC SHOCK PROTECTION** External shell protects against electrical hazards.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **LATERAL ADJUSTMENT DIVIDER** Side adjustment points on chinstrap for secure fit.
- **ADVANCED ECO-LEATHER CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- **EARMUFF ADAPTER ATTACHMENT POINTS** For adapters to secure earmuffs.
- **RING TO HOOK** Chinstrap loop that securely attaches helmet to a harness.
- **REPLACEABLE LAMP CLIPS** 4 lamp attachment clips designed to be removable.

3

YEARS  
GUARANTEE

10

YEARS  
LIFE SPAN



SCAN FOR  
COMPLETE  
COLLECTION