# ARC VISOR ATP10 ANSI

# ΚΛ/Κ

ΕN

WVI00016



Full face protection that enables the wearer to work on or be in the vicinity of live parts with arc protection up to 10.0 cal/cm<sup>2</sup> (ASTM F2178-12). Recommended for use with balaclava. Securely flips up and down. Attaches directly to the 30 mm EURO Slots.

Compatible with KASK Zenith X2 (Zenith X2 MAX included) and Primero helmet series.

### **TECHNICAL DETAILS**



**STANDARD** EN ISO 16321-1 ANSI Z87.1 + ASTM F2178 CSA Z94.3





# **TECHNOLOGIES**



#### PANORAMIC LENS

Developed to maximize visibility with minimal viewing distortion.

#### **STABLE CARRIER**

Reinforced face shield carrier for added protection and durability.



<del>©, ~</del>

#### > CRI 95

Designed with excellent Color Rendering Index performance for greater color contrast and visibility.

# **CE MARKINGS**

CODE	COLOR	MARKING
WVI00016	SMOKE	ΚΛ/Κ
		CLASS 1
		MM / YYYY 4 2 2 0 3 1
		く 低 1883 と 低 0843
		16321 KASK UL 2 E GS-ET-29 8-1-0 APC 1 ATPV 10 cal/cm <sup>2</sup> ANSI / ISEA 787.1
		KASK Z87+ U6 CSA Z94.3
		KASK 2.0

# **ADDITIONAL INFORMATION**

**COMPATIBLE WITH GLASSES** 

Designed for use with corrective glasses.

#### GUARANTEE

3 years starting from the date of purchase.

#### LIFE SPAN

10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

#### CLEANING

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.



CASK AMERICA INC / 301 W Summit Ave, Charlotte NC 28203 USA / +1 704 960 4851 / info@kaskamerica.us 🕞 💿 🕞 kask-safety.co